

JMC CARRYING PLUS

DIESEL T822



	Model	Open Box	Closing Box	Tipper	Refrigerator
Dimention	Cabin type	Single Cabin	Single Cabin	Single Cabin	Single Cabin
	Wheelbase(mm)	3360	3360	3360	3360
	Cabin width(mm)	2060	2060	2060	2060
	Overall Dimension Cargo body L*W*H(mm)"	5920*2180*2465	5990*2180*3135	5750*2150*2225	6010*2300*3275
	Cargo size L*H(mm)	SC: 4200*440	4200*2100*2100mm	3886*2000*500mm	4000*2100*2100
Powertrain	Engine	JX493	JX493	JX493	JX493
	Displacement(cc)	2771	2771	2771	2771
	Max.Output(hp)	120	120	120	120
	Max.Torque(n.m)	330	330	330	330
	Gearbox Type	5MT	5MT	5MT	5MT
	Fuel Tank Capacity (L)	125	125	125	125
	Rear axle speed ratio	5.571	5.571	5.571	5.571
	Brake type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Tire type	Dual Rear Tires	Dual Rear Tires	Dual Rear Tires	Dual Rear Tires
	Tire size	7.0R16 10PR	7.0R16 10PR	7.0R16 10PR	7.0R16 10PR
Break & Tire	Kerb weight(kg)	2050	2968	2830	2968
	GVW(kg)	6050	6050	6050	6050
	Payload	4000	3082	3220	3082
Weight	ABS	Std	Std	Std	Std
	Exhaust Brake	Std	Std	Std	Std
	Power Steering	Std	Std	Std	Std
	Sound alert for handbrake not released	Std	Std	Std	Std
Safety	Reminder of unfastened seat belt for driver	Std	Std	Std	Std
	Infotainment System	Std	Std	Std	Std
	(Bluetooth music / Bluetooth phone / USB music)	Std	Std	Std	Std
	Multifunction steering wheel	Std	Std	Std	Std
	Air conditioning	Std	Std	Std	Std
Comfort	Central locking(manual)	Std	Std	Std	Std
	Remote key	Std	Std	Std	Std
	Power windows	Std	Std	Std	Std
	One-touch window lift--driver	Std	Std	Std	Std
	Remote key control glass one-touch lift	Std	Std	Std	Std
	Driver armrest	Std	Std	Std	Std
	Headlight delay off	Std	Std	Std	Std
	Driver overhead storage box	Std	Std	Std	Std
	USB charging port	Std	Std	Std	Std
	Overhead storage box mounted USB port	Std	Std	Std	Std
	12V Socket/ Power Port DC 12V Outlet	Std	Std	Std	Std
	Speed-sensitive automatic door locking	Std	Std	Std	Std

Manufacture Warranty 6 years/150,000km

JMC CARRYING PLUS

DIESEL T822



Refrigerator Specifications		RV580
Temp Range		-20°C~30°C
Refrigerant		R-404A
Charge (kg)		2.5
Cooling Capacity (W)		A.T.P. U.N Standard @30°C (Ambient)
Engine Power	°C 0	5050
	°C 20-	2550
Cooling Capacity (W)		A.R.I. US Standard @38°C (Ambient)
Engine Power	°C 0	4900
	°C 18-	2520
Compressor		
Model		TK16
Number of Cylinder		6
Displacement(cm3)		163
Evaporator Blower Performance		
Flow Rate(m³/h)		2500
Velocity(m/s)		3
Electric option		
Voltage/Phase/Frequency/Current		/
Total Current Consumption on the Road(A)		
12 VDC		44
24 VDC		22
Weight(KG)		
Condenser		35
Evaporator		30
Compressor		4.7
Manufacture Warranty 6 years/150,000km		